







- [9] H. Banno, K. Ogura, H. Sobue, and K. Ohya, "Piezoelectric and acoustic properties of piezoelectric flexible composites," *Jpn. J. Appl. Phys.*, vol. 26, pp.153–155,1987.
- [10] R. Mansour, O. A. Omoniyi, R. O'Leary and J. F. C. Windmill, "Fabrication of Ultraviolet-Curable Piezoelectric Composite for Sensor and Actuator Applications," *2018 IEEE SENSORS*, New Delhi, 2018, pp. 1-4. <https://doi.org/10.1109/ICSENS.2018.8589943>
- [11] J. R. Giniewicz, K. Duscha, R. E. Newnham, and A. Safari, "0- 3 Composites for hydrophone applications," presented at IEEE Int. Symp. Appl. Ferroelect., Bethlehem, PA, 1986.
- [12] Domingo-Roca, R., Jackson, J. C., & Windmill, J. F. C. Bioinspired 3D-printed piezoelectric device for acoustic frequency separation. In *Proceedings of IEEE Sensors* (Vol. 2017–December, pp. 1–3). Institute of Electrical and Electronics Engineers Inc. <https://doi.org/10.1109/ICSENS.2017.8234384>
- [13] Yao, K., & Tay, F. E. H. Measurement of longitudinal piezoelectric coefficient of thin films by a laser-scanning vibrometer. *IEEE Transactions on Ultrasonics, Ferroelectrics, and Frequency Control*. <https://doi.org/10.1109/TUFFC.2003.1182115>